


NOTES

- A: MODEL NAME, OPTION, INPUT VOLTAGE RANGE, NOMINAL OUTPUT VOLTAGE, MAXIMUM OUTPUT CURRENT AND COUNTRY OF MANUFACTURE ARE SHOWN HERE IN ACCORDANCE WITH THE SPECIFICATIONS.
- B: M3 EMBOSSED, TAPPED AND COUNTERSUNK HOLES (5) FOR CUSTOMER CHASSIS MOUNTING. SCREWS MUST NOT PROTRUDE INTO POWER SUPPLY BY MORE THAN 6mm/m.
- C: $\phi 3.5$ HOLES (3) FOR CUSTOMER CHASSIS MOUNTING. (USE M3 MOUNTING SCREWS.)
- D: REMOTE ON/OFF CONTROL CONNECTOR --- OPTION B2B-XH-A (JST)

ACCESSORIES

- * COVER FOR BARRIER STRIP TERMINAL
- * HOUSING: XHP-2 (JST), TERMINAL: BXH-001T-P0.6 (JST) OR SXH-001T-P0.6 (JST) --- OPTION

HAND CRIMPING TOOL : YC-110R (JST) OR YRS-110 (JST)



OPTIONAL MODELS

MODEL	COVER	REMOTE ON/OFF CONTROL
JWS50-*		
JWS50-*/A	○	
JWS50-*/R		○
JWS50-*/RA	○	○

(unit : mm)

MODEL	JWS50
DENSEI-LAMBDA	
A157-02-01C	