

HWS3000G

A291-01-01A

SPECIFICATIONS (1/3)

ITEMS	MODEL	HWS3000G -24	HWS3000G -48	HWS3000G -60	HWS3000G -130	
INPUT RATING						
Input Voltage Range	(*13)(*23)	-	85- 265VAC (47-63Hz)			
Efficiency (Typ.)	100/115VAC	%	89	90	90	91
	(*2) 200/230VAC	%	91	92	92	93
Input Current (Typ.)	100/115VAC	A	17.4	17.3	17.2	17.1
	(*2) 200/230VAC	A	17.4	17.2	17.2	17.1
Power Factor (Typ.)	100VAC	-	0.97			
	(*2) 200VAC	-	0.95			
Inrush Current (Typ.)	100VAC	A	30 at 1st Inrush, 80 at 2nd Inrush			
	(*2),(*3) 200VAC	A	60 at 1st Inrush, 80 at 2nd Inrush			
Leakage Current	(*4)	-	LESS THAN 0.85 mA (240VAC , 60Hz)			
OUTPUT RATING						
Nominal Output Voltage		V	24	48	60	130
Maximum Output Voltage	(*1)	V	28.8	52.8	66.0	156.0
Maximum Output Current (85VAC≤Vin≤132VAC)	(*24)	A	62.5	31.3	25	11.6
Maximum Output Current (170VAC≤Vin≤265VAC)	(*24)	A	125	62.6	50	23.2
Maximum Output Power (85VAC≤Vin≤132VAC)		W	1500	1502.4	1500	1508
Maximum Output Power (170VAC≤Vin≤265VAC)		W	3000	3004.8	3000	3016
CONSTANT VOLTAGE MODE						
Output Voltage Range by adjustment trimmer	(*1)	V	19.2 - 28.8	38.4 - 52.8	48.0 - 66.0	104.0 - 156.0
Output Voltage Range by Programming	(*1)(*5)	V	0 - 28.8	0 - 52.8	0 - 66.0	0 - 156.0
Maximum Line Regulation	(*6)	mV	96	192	240	520
Maximum Load Regulation	(*7)	mV	192	384	480	1040
Temperature Coefficient		-	0.02%/°C			
Maximum Ripple & Noise	0 ≤ Ta ≤ 70°C	mVp-p	300	400	500	866
	(*8) -20 ≤ Ta < 0°C	mVp-p	360	480	600	1083
Hold-up Time (Typ.)		-	20ms at 1500W, 10ms at 3000W			
Remote Sensing		-	Possible			
Output Voltage External Control Using CV Terminal		-	Apply external voltage or current : 1 - 5V or 4 - 20mA Output Voltage : 0% - Nominal output voltage			
Output Voltage External Control Using Modbus RTU	(*17)	-	0-4,000 (Output Voltage : 0% - Nominal output voltage)			
CONSTANT CURRENT MODE						
Output Current External Control Range	(*1)(*11) (85VAC≤Vin≤132VAC)	A	0 - 62.5	0 - 31.3	0 - 25.0	0 - 11.6
Output Current External Control Range	(*1)(*11) (170VAC≤Vin≤265VAC)	A	0 - 125.0	0 - 62.6	0 - 50.0	0 - 23.2
Maximum Line Regulation (85VAC≤Vin≤132VAC)	(*6)	mA	250	125.2	100	46.4
Maximum Line Regulation (170VAC≤Vin≤265VAC)	(*6)	mA	500	250.4	200	92.8
Maximum Load Regulation (85VAC≤Vin≤132VAC)	(*12)	mA	500	250.4	200	92.8
Maximum Load Regulation (170VAC≤Vin≤265VAC)	(*12)	mA	1000	500.8	400	185.6
Temperature Coefficient		-	0.02%/°C			
Output Current External Control Using CC Terminal	(85VAC≤Vin≤132VAC)	-	Apply external voltage or current : 1 - 3V or 4 - 12mA Output Current : 0% - Maximum output Current			
Output Current External Control Using Modbus RTU	(*17) (85VAC≤Vin≤132VAC)	-	0-2,000 Output Current : 0% - Maximum output Current			
Output Current External Control Using CC Terminal	(170VAC≤Vin≤265VAC)	-	Apply external voltage or current : 1 - 5V or 4 - 20mA Output Current : 0% - Maximum output Current			
Output Current External Control Using Modbus RTU	(*17) (170VAC≤Vin≤265VAC)	-	0-4,000 Output Current : 0% - Maximum output Current			

HWS3000G

SPECIFICATIONS (2/3)

ITEMS	MODEL	HWS3000G -24	HWS3000G -48	HWS3000G -60	HWS3000G -130
PROTECTION					
Over Current Protection (85VAC≤Vin≤132VAC)	(*9) A	65.6 <	32.8 <	26.2 <	12.1 <
Over Current Protection (170VAC≤Vin≤265VAC)	(*9) A	131.2 <	65.7 <	52.5 <	24.3 <
Over Voltage Protection	(*10) V	30.4 - 31.5	56.1 - 58.1	70.2 - 72.6	165.1 - 170.3
ANALOG PROGRAMMING AND MONITORING					
Remote ON/OFF Control	-	Possible			
Parallel Operation	(*14) -	Possible, Current balancing function is provided			
Series Operation	(*15) -	Possible, Voltage balancing function is provided			
Output Voltage Monitor using VB terminal	-	Output Voltage : 0% - Nominal output voltage VB terminal voltage : 1 - 5V			
Output Current Monitor using CB terminal (85VAC≤Vin≤132VAC)	(*16) -	Output Current : 0% - Maximum output Current CB terminal voltage : 1 - 3V			
Output Current Monitor using CB terminal (170VAC≤Vin≤265VAC)	(*16) -	Output Current : 0% - Maximum output Current CB terminal voltage : 1 - 5V			
Monitoring Signal	-	Power Fail(VPF, CPF), AC Fail(ACF) (Open Collector Output)			
COMMUNICATION					
Digital Communication	(*17) -	Modbus RTU (RS-485)			
AUXILIARY OUTPUT					
Output Voltage (Typ.)	V	5			
Maximum Output Current	A	2			
ENVIRONMENT					
Operating Temperature	(*18) -	-20 to +70°C, Guarantee Start up : -40 to -20°C			
Storage Temperature	-	-40°C to +85°C			
Operating Humidity	-	20 to 90%RH (Non Condensing)			
Storage Humidity	-	10 to 95%RH (Non Condensing)			
Vibration	-	At no operating, 10 - 55Hz (Sweep for 1min) 19.6m/s ² Constant, X,Y,Z 1hour each.			
Shock	(*19)(*20) -	Less than 196m/s ²			
Cooling	(*21) -	Forced air cooling (Internal FAN)			
ISOLATION					
Withstand Voltage	-	Input-FG : 2.0kVAC (20mA) for 1min. Input-Output : 3.0kVAC (20mA) for 1min. Input-Signal, AUX : 3.0kVAC (20mA) for 1min. Output-Signal, AUX : 2.0kVAC (20mA) for 1min. Output-FG : 1.5kVAC (20mA) for 1min.			
Isolation Resistance	-	More than 100MΩ at 25°C and 70%RH, Output - FG 500VDC			
STANDARD AND COMPLIANCE					
Safety	(*13) -	Approved by IEC/EN/UL/CSA 62368-1 (Altitude ≤ 5,000m) Approved by IEC/EN62477-1 (OVC III) (Altitude ≤ 2,000m) Designed to meet Den-an Appendix 12 (J62368-1)			
Conducted Emission	(*19) -	Designed to meet EN55011/EN55032-A, FCC-ClassA, VCCI-A			
Radiated Emission	(*19) -	Designed to meet EN55011/EN55032-A, FCC-ClassA, VCCI-A			
Harmonic Current	(*19) -	Designed to meet IEC61000-3-2			
Immunity	(*19)(*22) -	Designed to meet IEC61000-6-2 (IEC61000-4-2, -3, -4, -5, -6, -8, -11)			
Line DIP	(*19) -	Designed to meet SEMI-F47 (at 200VAC)			

HWS3000G

SPECIFICATIONS (3/3)

ITEMS	MODEL	HWS3000G -24	HWS3000G -48	HWS3000G -60	HWS3000G -130
MECHANICAL					
Weight (Typ.)	kg	2.3			
Size (W x H x D)	mm	150x 61 x 270 (Refer to Outline Drawing)			

*Read Instruction Manual (A291-04-01_) carefully, before using the power supply unit.

=NOTES=

- *1. When using the product above the nominal output voltage, derate the output current so that the maximum output power is not exceeded. Please refer to Fig. A.
(*a) Limited by maximum output power value
- *2. Ta=25°C, nominal output voltage and maximum output power.
- *3. Not applicable for the inrush current to Noise Filter for less than 0.2ms.
- *4. Measured by the each measuring method of UL, CSA, EN and Den-an (at 60Hz), Ta=25°C.
- *5. Output voltage external control range using CV terminal and communication function.
- *6. 85-132VAC/170-265VAC, constant load.
- *7. No load - Full load, constant input voltage.
- *8. Please refer to Instruction Manual (A291-04-01_) for measurement of ripple noise voltage.
- *9. Constant current limit with automatic recovery.
If the overcurrent condition continues for more than 30 seconds, the output will shut down.
A dynamic overload, such as an output short circuit, will cause the output to shut down.
- *10. OVP circuit will shut the output down, manual reset.
- *11. Output voltage external control range using CC terminal and communication function.
- *12. Minimum output voltage - Nominal output voltage, constant input voltage.
- *13. For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100 - 120VAC/200 - 240VAC(50-60Hz).
- *14. Up to 10 units.
- *15. Up to 3 units.
- *16. Use a measuring instrument whose input impedance is 500kΩ or more.
- *17. <Communication function example>
•Control of output voltage and output current. •Remote ON/OFF control.
•Product status including product life can be monitored.
•Operation history can be obtained.(OCP,OVP,AC Fail, etc.) etc.
Refer to instruction manual (A291-04-01_) and communication manual (A291-04-02_).

Fig.A





Fig.B




(*) Maximum output power depends on output voltage. Refer to output ratings for values.

- *18. Output Derating
- Refer to OUTPUT CURRENT vs. AMBIENT TEMPERATURE (A291-01-02_).
At -40 to -20°C, the electrical characteristics are not guaranteed.
- *19. The specifications are based on TDK-Lambda standard measurement conditions.
The power supply is considered a component which will be installed into a final equipment.
The final equipment should be re-evaluated that it meets EMC, vibration and shock requirement.
- *20. Mounting A only.
- *21. Variable speed fan. Fan noise is 45dB (typ) at 25°C and 70% load.
- *22. Signal and control ports interface cables length: Less than 3m, DC output power port cables length: Less than 30m.
- *23. When changing the input voltage from 100Vac line to 200Vac line, or from 200Vac line to 100Vac line, first cut off the input and wait 60 seconds before changing.
- *24. Please refer to Fig.B for maximum output power of each input voltage.

OUTPUT DERATING

A291-01-02

Ta (°C)	OUTPUT CURRENT (%)
	MOUNTING A,B
-20 to +50	100
70	50



MOUNTING A
(STANDARD MOUNTING)

MOUNTING B

