

**SPECIFICATIONS**

A178-01-01/A-D

ITEMS	MODEL		JWT75-522/A			JWT75-5FF/A			JWT75-525/A			
			V1	V2	V3	V1	V2	V3	V1	V2	V3	
1	Nominal Output Voltage	V	+5	+12	-12	+5	+15	-15	+5	+12	-5	
2	Minimum Output Current (*1)	A	0.8	0	0	0.8	0	0	0.8	0	0	
3	Maximum Output Current	A	8.0	4.0	0.5	8.0	3.2	0.5	8.0	4.0	0.5	
4	Maximum Output Power / CH	W	40	48	6	40	48	7.5	40	48	2.5	
5	Total Allowable Output Power	W		75			75			75		
6	Efficiency (Typ) (*2)	%					72					
7	Input Voltage Range (*3)	-				85 - 265VAC (47 - 63Hz) or 120 - 330VDC						
8	Input Current (100/200VAC) (Typ) (*2)	A					1.2 / 0.6					
9	Inrush Current (Typ) (*2,4)	A				14A at 100VAC, 28A at 200VAC, Ta=25°C, Cold Start						
10	PFHC	-				Designed to meet EN61000-3-2						
11	Power Factor (100/200VAC) (Typ) (*2)	-				0.99 / 0.93						
12	Output Voltage Range	-	5.0 - 5.25	Fixed	Fixed	5.0 - 5.25	Fixed	Fixed	5.0 - 5.25	Fixed	Fixed	
13	Output Voltage Accuracy	-	-	±5%	±5%	-	±5%	±5%	-	±5%	±5%	
14	Maximum Ripple & Noise (*5)	0≤Ta≤55°C -10≤Ta≤0°C	mV	120	150	150	120	150	150	120	150	
			mV	160	180	180	160	180	180	160	180	
15	Maximum Line Regulation (*6)	mV	20	48	48	20	60	60	20	48	20	
16	Maximum Load Regulation (*7)	mV	40	100	150	40	120	150	40	100	100	
17	Temperature Coefficient	-				V1,V2:Less than 0.02% / °C, V3:Less than 0.03% / °C						
18	Over Current Protection (*8)	A				More than 105%						
19	Over Voltage Protection (*9)	V	5.7 - 7.0	-	-	5.7 - 7.0	-	-	5.7 - 7.0	-	-	
20	Hold-Up Time (Typ) (*10)	-				20 ms						
21	Leakage Current (*11)	-				0.75mA MAX, 0.2mA(Typ) at 100VAC / 0.44mA(Typ) at 230VAC						
22	Parallel Operation	-					-					
23	Series Operation	-					-					
24	Operating Temperature (*12)	-				-10 to +55°C (-10 to +45°C :100%, +55°C :60%)						
25	Operating Humidity	-				30 to 90%RH						
26	Storage Temperature	-				-30 to +85°C						
27	Storage Humidity	-				10 to 95%RH						
28	Cooling	-				Convection Cooling						
29	Withstand Voltage	-				Input - FG:2kVAC(20mA), Input - Output:3kVAC (20mA) Output - FG:500VAC(100mA), for 1min.						
30	Isolation Resistance	-				More than 100MΩ at 25°C and 70%RH Output - FG : 500VDC						
31	Vibration	-				At no operating, 10-55Hz (Sweep for 1min) 19.6m/s² Constant, X,Y,Z 1h each.						
32	Shock (In package)	-				Less than 196.1m/s²						
33	Safety (*13)	-				Approved by UL62368-1, CSA62368-1, EN62368-1, UL60950-1, CSA60950-1, EN60950-1 (Expire date of 60950-1 : 20/12/2020) Designed to meet DENAN						
34	Conducted Emission	-				Designed to meet EN55011 / EN55032-B, FCC-ClassB, VCCI-B.						
35	Radiated Emission	-				Designed to meet EN55011 / EN55032-B, FCC-ClassB, VCCI-B.						
36	Weight (Typ)	-				700g						
37	Size (W x H x D)	mm				42 x 92 x 188 (Refer to Outline Drawing)						

\*Read instruction manual carefully, before using the power supply unit.

## =NOTES=

- \*1. For V2, V3 stability, to keep V1 minimum output current.
- \*2. At 100/200VAC, Ta=25°C and maximum output power.
- \*3. For cases where conformance to various safety specs (UL, CSA, EN) are required, input voltage range will be 100 - 240VAC(50/60Hz).
- \*4. No applicable for the inrush current to Noise Filter less than 0.2ms.
- \*5. Measure with JEITA RC-9131 probe, Bandwidth of scope :100MHz.
- \*6. 85 - 265VAC, constant load.
- \*7. Minimum load - Full load, constant input voltage.
- \*8. Constant current limit with automatic recovery.
- \*9. OVP circuit will shut down all outputs, manual reset (Line recycle).
- \*10. At 100/200VAC nominal output voltage and maximum total output power.
- \*11. Measured by the each measuring method of UL, CSA, EN and DENAN (at 60Hz), Ta=25°C.
- \*12. Ratings - Derating at standard mounting.
  - Load (%) is percent of maximum output power or maximum output current, whichever is greater.
  - As for other mountings, refer to derating curve (A178-01-02/A-).
- \*13. As for DENAN, designed to meet at 100VAC.

## OUTPUT DERATING

A178-01-02/A

Ta(°C)	LOAD(%)			
	MOUNTING A	MOUNTING B	MOUNTING C	MOUNTING D
-10 ~+30	100	100	100	100
35	100	100	80	80
40	100	80	60	60
45	100	60		
50	80			
55	60			

OUTPUT DERATING CURVE

