

PAQ50S48-*

EVALUATION DATA

型式データ

DWG.No. C165-53-01B

DENSEI-LAMBDA

INDEX

| 1. 測定方法 | Evaluation Method | PAGE |
|---------|--|---------|
| 1.1 | 測定回路 Circuits used for determination | T-1~5 |
| | (1) 静特性 Steady state data | |
| | (2) 通電ドリフト特性 Warm up voltage drift characteristics | |
| | (3) 過電流保護特性 Over current protection (OCP) characteristics | |
| | (4) 過電圧保護特性 Over voltage protection (OVP) characteristics | |
| | (5) 出力立ち上がり特性 Output rise characteristics | |
| | (6) 出力立ち下がり特性 Output fall characteristics | |
| | (7) 出力立ち上がり特性 (ON/OFFコントロール時) Output rise characteristics with ON/OFF CONTROL | |
| | (8) 出力立ち下がり特性 (ON/OFFコントロール時) Output fall characteristics with ON/OFF CONTROL | |
| | (9) 過渡応答 (負荷急変) 特性 Dynamic load response characteristics | |
| | (10) 入力サージ電流 (突入電流) 特性 Inrush current characteristics | |
| | (11) 出力リップル、ノイズ波形 Output ripple and noise waveform | |
| | (12) EMI特性 Electro-Magnetic Interference characteristics | |
| 1.2 | 使用測定機器 List of equipments used | T-6 |
| 2. | 特性データ Characteristics | |
| 2.1 | (1) 入力・負荷・温度変動 Regulation - line and load, temperature drift | T-7~8 |
| | (2) 出力電圧・リップル電圧対入力電圧 Output voltage and ripple voltage v.s. input voltage | T-9~10 |
| | (3) 効率・入力電流対出力電流 Efficiency and input current v.s. output current | T-11~13 |
| | (4) 効率対入力電圧 Efficiency v.s. input voltage | T-14~16 |
| | (5) 効率対周囲温度 Efficiency v.s. ambient temperature | T-17~19 |
| 2.2 | 通電ドリフト特性 Warm up voltage drift characteristics | T-20 |
| 2.3 | 過電流保護特性 Over current protection (OCP) characteristics | T-21~24 |
| 2.4 | 過電圧保護特性 Over voltage protection (OVP) characteristics | T-25 |
| 2.5 | 出力立ち上がり特性 Output rise characteristics | T-26~27 |
| 2.6 | 出力立ち下がり特性 Output fall characteristics | T-28~29 |
| 2.7 | 出力立ち上がり特性 (ON/OFFコントロール時) Output rise characteristics with ON/OFF CONTROL | T-30~31 |
| 2.8 | 出力立ち下がり特性 (ON/OFFコントロール時) Output fall characteristics with ON/OFF CONTROL | T-32~33 |

2.9 過渡応答（負荷急変）特性 Dynamic load response characteristics T-34~35

2.10 入力サージ電流（突入電流）特性 Inrush current waveform T-36

2.11 出力リップル、ノイズ波形 Output ripple and noise waveform T-37

2.12 EMI特性 Electro-Magnetic Interference characteristics


 VCCI class A 対応アプリケーションシステム

 VCCI class A application system T-38~42

使用記号 Terminology used

| | Definition | |
|------|-------------|---------------------|
| Vin | 入力電圧 | Input Voltage |
| Vout | 出力電圧 | Output Voltage |
| VCNT | CNT電圧 | CNT Voltage |
| Iin | 入力電流 | Input Current |
| Iout | 出力電流 | Output Current |
| Ta | 周囲温度 | Ambient Temperature |


1. 測定方法 Evaluation Method
 1.1 測定回路 Circuits used for determination
 (1) 静特性 Steady state data




- (2) 通電ドリフト Warm up voltage drift characteristics

静特性と同じ
 Same as Steady state data

- (3) 過電流保護特性 Over current protection (OCP) characteristics




(4) 過電圧保護特性 Over voltage protection (OVP) characteristics



C1: 1µF Ceramic Capacitor
C2: 10µF Tantalum Capacitor

l_1 : 50mm

(5) 出力立ち上がり特性 Output rise characteristics



C1: 1µF Ceramic Capacitor
C2: 10µF Tantalum Capacitor

l_1 : 50mm


(6) 出力立ち下がり Output fall characteristics

出力立ち上がり特性と同じ

Same as output rise characteristics

(7) 出力立ち上がり特性 (ON/OFFコントロール時)

Output rise characteristics with ON/OFF CONTROL



C1: 1uF Ceramic Capacitor
C2: 10uF Tantalum Capacitor

l_1 : 50mm


(8) 出力立ち下がり特性 (ON/OFFコントロール時)

Output fall characteristics with ON/OFF CONTROL

出力立ち上がり特性 (ON/OFFコントロール時) と同じ

Same as output rise characteristics with ON/OFF CONTROL


(9) 過渡応答(負荷急変)特性 Dynamic load response characteristics



C1: 1uF Ceramic Capacitor
C2: 10uF Tantalum Capacitor

l_1 : 50mm


(10) 入力サージ電流 (突入電流) 特性 Inrush current characteristics



C1: 1uF Ceramic Capacitor
C2: 10uF Tantalum Capacitor

l_1 : 50mm

(11) 出力リップル、ノイズ波形 Output ripple and noise waveform




C1: 1uF Ceramic Capacitor
C2: 10uF Tantalum Capacitor
C3: 4700pF Film Capacitor


R1: 50 Ω
 l_1 : 50mm

(12) EMI 特性 Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ) Conducted Emission Noise




(b) 雑音電界強度 (輻射ノイズ) Radiated Emission Noise



(1) VCC class A 対応対応アプリケーションシステム

VCCI class A application system



- $L1$: 1mH
- $C1$: 1 μ F Ceramic Capacitor
- $C2$: 10 μ F Tantalum Capacitor
- $C3$: 1 μ F Film Capacitor
- $C4, C5$: 0.068 μ F Film Capacitor

- $C6$: 470 μ F Electrolytic Capacitor
- $C7, C8$: 0.033 μ F Film Capacitor
- $C9$: 2200pF Ceramic Capacitor
- $\varnothing 1$: 50mm

1.2 使用測定機器 List of equipment used

| | EQUIPMENT USED | MANUFACTURER | MODEL NO. |
|----|------------------------------|-----------------|-------------|
| 1 | OSCILLO SCOPE | HITACHI DENSHI | V-1100A |
| 2 | DIGITAL STORAGE OSCILLOSCOPE | IWATSU-LECROY | LT364L |
| 3 | DIGITAL MULTIMETER | ADVANTEST | R6341A |
| 4 | DIGITAL POWER METER | YOKOGAWA ELECT. | WT110 |
| 5 | CURRENT PROBE/AMPLIFIER | TEKTRONIX | A6303/AM503 |
| 6 | SHUNT REGISTER | YOKOGAWA ELECT. | 2215 |
| 7 | X-Y RECORDER | GRAPHTEC | WX4309 |
| 8 | CONTROLLED TEMP. CHANBER | TABAI ESPEC | SH-240 |
| 9 | SPECTRUM ANALYZER | ROHDE & SCHWARZ | FSA |
| 10 | EMI TEST RECEIVER | ROHDE & SCHWARZ | ESHS10 |
| 11 | EMI TEST RECEIVER | ROHDE & SCHWARZ | ESVS10 |
| 12 | RF RELAY MATRIX | ROHDE & SCHWARZ | PSU |
| 13 | AMN | KYORITU DENSHI | KNW-242 |
| 14 | ANTENNA(BICONICAL ANTENNA) | SCHWARZBECK | BBA9106 |
| 15 | DYNAMIC DUMMY LOAD | TAKASAGO | FK-1000L |
| 16 | AC POWER SUPPLY | KIKUSUI | PCR4000L |

2. 特性データ

2.1 静特性 Steady state data

(1) 入力、負荷、温度変動 Regulation - line and load, temperature drift

1.8V

1. Regulation - line and load

condition Ta : 25°C

Air Velocity : 2m/s

| Iout \ Vin | 36VDC | 48VDC | 76VDC | line regulation | |
|-----------------|---------|---------|---------|-----------------|--------|
| 0% | 1.7913V | 1.7913V | 1.7912V | 0.1mV | 0.006% |
| 50% | 1.7913V | 1.7913V | 1.7912V | 0.1mV | 0.006% |
| 100% | 1.7913V | 1.7913V | 1.7910V | 0.3mV | 0.017% |
| load regulation | 0.0mV | 0.0mV | 0.2mV | | |
| | 0.000% | 0.000% | 0.011% | | |

2. Temperature drift

conditions Vin : 48VDC

Iout : 100%

Air Velocity : 2m/s

| Ta | -40°C | 25°C | 85°C | temperature stability | |
|------|---------|---------|---------|-----------------------|--------|
| Vout | 1.7979V | 1.7913V | 1.7881V | 9.8mV | 0.544% |

3.3V

1. Regulation - line and load

condition Ta : 25°C

Air Velocity : 2m/s

| Iout \ Vin | 36VDC | 48VDC | 76VDC | line regulation | |
|-----------------|---------|---------|---------|-----------------|--------|
| 0% | 3.3037V | 3.3036V | 3.3037V | 0.1mV | 0.003% |
| 50% | 3.3038V | 3.3037V | 3.3035V | 0.3mV | 0.009% |
| 100% | 3.3038V | 3.3037V | 3.3034V | 0.4mV | 0.012% |
| load regulation | 0.1mV | 0.1mV | 0.3mV | | |
| | 0.003% | 0.003% | 0.009% | | |

2. Temperature drift

conditions Vin : 48VDC

Iout : 100%

Air Velocity : 2m/s

| Ta | -40°C | 25°C | 85°C | temperature stability | |
|------|---------|---------|---------|-----------------------|--------|
| Vout | 3.3062V | 3.3037V | 3.2935V | 12.7mV | 0.385% |

2. 特性データ

2.1 静特性 Steady state data

(1) 入力、負荷、温度変動 Regulation - line and load, temperature drift

5V

1. Regulation - line and load

condition Ta : 25°C

Air Velocity : 2m/s

| Iout \ Vin | 36VDC | 48VDC | 76VDC | line regulation | |
|------------|---------|---------|---------|-----------------|--------|
| 0% | 4.9971V | 4.9977V | 4.9968V | 0.9mV | 0.018% |
| 50% | 4.9975V | 4.9978V | 4.9971V | 0.7mV | 0.014% |
| 100% | 4.9972V | 4.9972V | 4.9961V | 1.1mV | 0.022% |
| load | 0.4mV | 0.6mV | 1.0mV | | |
| regulation | 0.008% | 0.012% | 0.020% | | |

2. Temperature drift

conditions Vin : 48VDC

Iout : 100%


Air Velocity : 2m/s

| Ta | -40°C | 25°C | 85°C | temperature stability | |
|------|---------|---------|---------|-----------------------|--------|
| Vout | 5.0064V | 4.9972V | 4.9808V | 25.6mV | 0.512% |

2.1 (2) 出力電圧、リップル電圧対入力電圧
Output voltage and ripple voltage vs input voltage


Conditions Iout : 100 %
 Ta : -40 °C -----
 25 °C -.-.-.-
 85 °C _____
 Air Velocity : 2 m/s

1.8V



Ta : -40 °C -----
 25 °C -.-.-.-
 85 °C _____
 Air Velocity : 2 m/s

3.3V



2.1 (2) 出力電圧、リップル電圧対入力電圧
Output voltage and ripple voltage vs input voltage

Conditions Iout : 100 %


Ta : -40 °C -----

25 °C - - - - -

85 °C _____

Air Velocity : 2 m/s


5V




2.1 (3) 効率、入力電流対出力電流
Efficiency and input current vs output current

Conditions V_{in} : 36 VDC -----
 : 48 VDC - - - - -
 : 76 VDC ————
 T_a : 25 °C
 Air Velocity : 2 m/s

1.2V



1.8V




2.1 (3) 効率、入力電流対出力電流


Efficiency and input current vs output current

Conditions V_{in} : 36 VDC -----
 : 48 VDC - - - - -
 : 76 VDC _____
 T_a : 25 °C
 Air Velocity : 2 m/s

2.5V



3.3V




2.1 (3) 効率、入力電流対出力電流

Efficiency and input current vs output current

Conditions Vin : 36 VDC -----
 : 48 VDC - - - - -
 : 76 VDC ————
 Ta : 25 °C
 Air Velocity : 2 m/s


5V




2.1 (4) 効率対入力電圧
Efficiency vs input voltage

Conditions Ta : 25 °C
 Iout : 50 % -----
 80 % -.-.-.-
 100 % _____
 Air Velocity : 2 m/s

1.2V




1.8V




2.1 (4) 効率対入力電圧
Efficiency vs input voltage

Conditions Ta : 25 °C
 Iout : 50 % -----
 80 % -.-.-.-.
 100 % _____
 Air Velocity : 2 m/s

2.5V




3.3V



2.1 (4) 効率対入力電圧
Efficiency vs input voltage

Conditions Ta : 25 °C
 Iout : 50 % -----
 80 % -.-.-.-.-
 100 % _____
 Air Velocity : 2 m/s


5V




2.1 (5) 効率対周囲温度
Efficiency vs ambient temperature

Conditions Vin : 48 VDC
Iout : 100 %
Air Velocity : 2 m/s

1.2V




1.8V




2.1 (5) 効率対周囲温度
Efficiency vs ambient temperature

Conditions Vin : 48 VDC
Iout : 100 %
Air Velocity : 2 m/s

2.5V




3.3V



2.1 (5) 効率対周囲温度
Efficiency vs ambient temperature

Conditions Vin : 48 VDC
Iout : 100 %
Air Velocity : 2 m/s

5V



2.2 通電ドリフト特性
Warm up voltage drift characteristics


Conditions Vin : 48 VDC

Iout : 100 %


Ta : 25 °C

Air Velocity : 2 m/s


1.8V



3.3V




5V




2.3 過電流保護特性
Over current protection (OCP) characteristics

Conditions Vin : 36 VDC -----
 : 48 VDC - - - - -
 : 76 VDC ————
 Ta : 25 °C

1.8V



3.3V




2.3 過電流保護特性

Over current protection (OCP) characteristics

Conditions Vin : 36 VDC -----
 : 48 VDC -.-.-.-.-
 : 76 VDC —————
Ta : 25 °C

5V




2.3 過電流保護特性


Over current protection (OCP) characteristics

Conditions Ta : -40 °C -----
 : 25 °C - - - - -
 : 85 °C _____
 Vin : 48 VDC

1.8V



3.3V




2.3 過電流保護特性

Over current protection (OCP) characteristics

Conditions Ta : -40 °C -----
 : 25 °C - - - - -
 : 85 °C —————
Vin : 48 VDC


5V




2.4 過電圧保護特性
Over voltage protection (OVP) characteristics

Conditions Vin : 48 VDC
Iout : 0 %
Ta : 25 °C


1.8V



3.3V



5V




2.5 出力立ち上がり特性
Output rise characteristics


PAQ50S48-*

Conditions Vin : 48 VDC
Iout : 0 %
Ta : 25 °C


1.8V



3.3V



5V




出力立ち上がり特性
Output rise characteristics


PAQ50S48-*

Conditions Vin : 48 VDC
Iout : 100 %
Ta : 25 °C


1.8V



3.3V



5V




2.6 出力立ち下がり特性
Output fall characteristics


PAQ50S48-*

Conditions Vin : 48 VDC
Iout : 0 %
Ta : 25 °C


1.8V



3.3V



5V




出力立ち下がり特性
Output fall characteristics


PAQ50S48-*

Conditions Vin : 48 VDC
Iout : 100 %
Ta : 25 °C


1.8V



3.3V



5V




2.7 出力立ち上がり特性 (ON/OFFコントロール時)
Output rise characteristics with ON/OFF CONTROL


PAQ50S48-*

Conditions Vin : 48 VDC
Iout : 0 %
Ta : 25 °C


1.8V



3.3V



5V




出力立ち上がり特性 (ON/OFFコントロール時)
Output rise characteristics with ON/OFF CONTROL


PAQ50S48-*

Conditions Vin : 48 VDC
Iout : 100 %
Ta : 25 °C


1.8V



3.3V



5V




2.8 出力立ち下がり特性 (ON/OFFコントロール時)
Output fall characteristics with ON/OFF CONTROL


PAQ50S48-*

Conditions Vin : 48 VDC
Iout : 0 %
Ta : 25 °C


1.8V



3.3V




5V




出力立ち下がり特性 (ON/OFFコントロール時)
Output fall characteristics with ON/OFF CONTROL

Conditions Vin : 48 VDC
Iout : 100 %
Ta : 25 °C


1.8V



3.3V




5V




2.9 過渡応答（負荷急変）特性
Dynamic load response characteristics

Conditions Vin : 48 VDC
Ta : 25 °C

1.8V




3.3V



2.9 過渡応答 (負荷急変) 特性
Dynamic load response characteristics

Conditions Vin : 48 VDC
Ta : 25 °C


5V



2.10 入力サージ電流 (突入電流) 特性
Inrush current waveform

Conditions Vin : 48 VDC
Iout : 100 %
Ta : 25 °C

3.3V



2.11 出力リップル、ノイズ波形
Output ripple and noise waveform


PAQ100S48-*

Conditions Vin : 48 VDC


Iout : 100 %

Ta : 25 °C


1.8V



3.3V



5V



2.12 EMI特性

Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ)

Conditions Vin : 48 VDC

Conducted Emission


Iout : 100 %

(1) VCCI class A 対応アプリケーションシステム


Ta : 25 °C

VCCI class A application system

1.8V



3.3V



EMI特性

Electro-Magnetic Interference characteristics

(a) 雑音端子電圧 (帰還ノイズ)

Conducted Emission

(1) VCCI class A 対応アプリケーションシステム


VCCI class A application system

Conditions Vin : 48 VDC

Iout : 100 %

Ta : 25 °C

5V



EMI特性

Electro-Magnetic Interference characteristics

(b) 雑音電界強度 (輻射ノイズ)

Conditions Vin : 48 VDC

Radiated Emission

Iout : 100 %


(1) VCCI class A 対応アプリケーションシステム

Ta : 25 °C


VCCI class A application system

1.8V

HORIZONTAL:



VERTICAL:



EMI特性

Electro-Magnetic Interference characteristics

(b) 雑音電界強度 (輻射ノイズ)

Conditions Vin : 48 VDC

Radiated Emission

Iout : 100 %


(1) VCCI class A 対応アプリケーションシステム

Ta : 25 °C


VCCI class A application system

3.3V

HORIZONTAL:



VERTICAL:



EMI特性

Electro-Magnetic Interference characteristics

(b) 雑音電界強度 (輻射ノイズ)

Conditions Vin : 48 VDC

Radiated Emission

Iout : 100 %


(1) VCCI class A 対応アプリケーションシステム

Ta : 25 °C

VCCI class A application system

5V

HORIZONTAL:



VERTICAL:

