

UL TEST REPORT AND PROCEDURE

Standard:	UL 62368-1, 3rd Ed, 2021-10-22 (Audio/video, information and communication technology equipment Part 1: Safety requirements) CAN/CSA C22.2 No. 62368-1:19, 3rd Ed, 2021-10-22 (Audio/video, information and communication technology equipment Part 1: Safety requirements)
Certification Type:	Component Recognition
CCN:	QQJQ2, QQJQ8 (Power Supplies for Use in Audio/Video, Information and Communication Technology Equipment)
Complementary CCN:	N/A
Product:	DC-To-DC Converters
Model:	<p>GQA24***A%%V-xxx -R, (PR); -R indicating RoHS compliance, or - (007) for unpotted or (-0P7) for potted.</p> <p>Where:</p> <ul style="list-style-type: none">- 24 represents nominal input voltage, with a 18-36 Vdc input, Max Input Current 9 A dc;- *** represents rated output current between 0 A - 2.5 A, *** maybe 1 to 3 digits, note that last digit is preceded by decimal point.- %%% represents rated output voltage, 48 Vdc nominal, Note that the third digit is preceded by a decimal point. Example 120 implies 12.0 Volts. with Max Output Power of 120 W- xxx represents alphanumeric characters which indicates non safety related feature set options- Optional -R indicating RoHS compliance, or (-007) for unpotted, or (-0P7) for potted) <p>GQA2W***A%%V-xxx-R, (PR); -R indicating RoHS compliance, or - (007) for unpotted or (-0P7) for potted.</p> <p>Where:</p> <ul style="list-style-type: none">- 2W represents nominal input voltage, with a 9 36 Vdc input, with a Max Input Current of 23 A- *** represents rated output current between 4.28 A - 28 A; *** maybe 1 to 3 digits, note that last digit is preceded by decimal point.- %%% represents rated output voltage between, 5 Vdc -28 Vdc, with Max Output Power of 150 W. Note that the third digit is preceded by a decimal point. Example 120 implies 12.0 Volts. with Max Output Power of 120 W.

	- xxx represents alphanumeric characters which indicates non safety related feature set options - Optional -R indicating RoHS compliance, or (-007) for unpotted, or (-0P7) for potted)
Rating:	Optional Rated Input: 36 VDC Max, 23 A Max Rated output: 48 VDC Max, 28 A Max, 150 W Max.
Applicant Name and Address:	TDK-LAMBDA AMERICAS INC 3000 TECHNOLOGY DR, SUITE 100 PLANO TX 75074 UNITED STATES

This is to certify that representative samples of the products covered by this Test Report have been investigated in accordance with the above referenced Standards. The products have been found to comply with the requirements covering the category and the products are judged to be eligible for Follow-Up Service under the indicated Test Procedure. The manufacturer is authorized to use the UL Mark on such products which comply with this Test Report and any other applicable requirements of UL LLC ('UL') in accordance with the Follow-Up Service Agreement. Only those products which properly bear the UL Mark are considered as being covered by UL's Follow-Up Service under the indicated Test Procedure.

The applicant is authorized to reproduce the referenced Test Report provided it is reproduced in its entirety.

UL authorizes the applicant to reproduce the latest pages of the referenced Test Report consisting of the first page of the Specific Technical Criteria through to the end of the Conditions of Acceptability.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL.

Prepared By: Oliver Trinh/Mengis Tesfay /
Project Handler

Reviewed By: Michael Lockhart / Reviewer

Supporting Documentation

The following documents located at the beginning of this Procedure supplement the requirements of this Test Report:

A. Authorization - The Authorization page may include additional Factory Identification Code markings.

B. Generic Inspection Instructions -

- i. Part AC details important information which may be applicable to products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of this Test Report.
- ii. Part AE details any requirements which may be applicable to all products covered by this Procedure. Products described in this Test Report must comply with any applicable items listed unless otherwise stated in the body of each Test Report.
- iii. Part AF details the requirements for the UL Certification Mark which is not controlled by the technical standard used to investigate these products. Products are permitted to bear only the Certification Mark(s) corresponding to the countries for which it is certified, as indicated in each Test Report.

Product Description

The product is a component type DC to DC power module with a planar power transformer. The converter is provided with input terminal pins for factory installation onto a printed wiring board with a connection to a dc source of supply and output terminal pins. The product employs a multilayer PWB planar transformer.

Model Differences

The GQA product is available in four mechanical configurations that both use the same transformer core set and output filter inductor core set except for the air gap and number of turns embedded in the pcb. The four mechanical configurations use the same pcb and part set, the difference between them is the physical size of the base plate that is mounted on the unit. One house-keeping transformer is used in GQA platform. The house keep magnetic is used to deliver the drive pulses and bias power across the isolation boundary from secondary to the primary side.

All models are similar except for input rating, output rating, and number of turns for the power transformer.

Test Item Particulars

Product group	--
Classification of use by	Instructed person
Supply Connection	not mains connected: ES1
Supply tolerance	None
Supply connection – type	No direct connection to Mains
Considered current rating of protective device	N/A, No direct connection to Mains A; N/A
Equipment mobility	for building-in
Over voltage category (OVC)	OVC I
Class of equipment	Not Classified
Special installation location	N/A 0
Pollution degree (PD)	PD 2
Manufacturer's specified Tma (°C)	25
IP protection class	IPX0

Power systems	--
Altitude during operation (m)	2000 m or less
Altitude of test laboratory (m)	App 105 m
Mass of equipment (kg)	0.088

Technical Considerations

- The product was submitted and evaluated for use at the maximum ambient temperature (Tma) permitted by the manufacturer’s specification of : 25°C
- The product is intended for use on the following power systems : No direct connection
- Considered current rating of protective device as part of the building installation (A) : N/A. For building in.
- Mains supply tolerance (%) or absolute mains supply : No direct connection
- The equipment disconnect device is considered to be : N/A
- The following are available from the Applicant upon request : Installation (Safety) Instructions / Manual
- The product was investigated to the following additional standard : EN IEC 62368-1:2020+A11:2020

Engineering Conditions of Acceptability

For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC. When installed in an end-product, consideration must be given to the following:

- The following product-line tests are conducted for this product : Electric Strength
- The following output circuits are at ES1 energy levels : All
- The following output circuits are at PS3 energy levels : Output Terminal
- The investigated Pollution Degree is : 2
- The following end-product enclosures are required : Electrical, Fire
- The output circuit is considered PS3
- Heating Test shall be evaluated in end product.
- Classification of PIS has not been conducted. Therefore, all electrical components and conductors including printed wirings were assumed to be arcing/resistive PIS.
- Unit intended for building-in and supplied power from secondary circuit which is isolated from primary circuit by double or reinforced insulation.

Additional Information

This report is based on CB report references E220248-A6010-CB-1 and CB Test Certificate Ref. US-34826-UL, respectively which was previously evaluated to UL 62368-1, 2nd Edition, 2014-12-01, CSA C22.2 No. 62368-1-14, 2nd Edition, 2014-12, and IEC 62368-1:2014. Testing conducted in accordance with IEC UL 62368-1, 2nd Edition, 2014-12-01, CSA C22.2 No. 62368-1-14, 2nd Edition, 2014-12, and IEC 62368-1:2014, was deemed equivalent to the test required per UL62368-1, 3rd Ed December 13, 2019; CAN/CSA-C22.2 No. 62368-1, 3rd Ed December 13, 2019; and IEC62368-1:2018, 3rd Ed.

All original sample and test dates are noted in the testing portion of this report.

The nameplate included in the report is representative of all models covered under this report.

Additional Standards

The product fulfills the requirements of: EN IEC 62368-1:2020+A11:2020

Markings and Instructions

Clause Title	Marking or Instruction Details
--------------	--------------------------------

Equipment identification marking – Manufacturer identification	Listee's or Recognized Company's name, Trade Name, Trademark or File Number
Equipment identification marking – model identification	Model Number
Special Instructions to UL Representative Units can be fully manufactured in either the Malaysia or Plano, TX location; however, it is also possible that completed units can go back to either factory for rework where a new product label can be applied based on the location that completed the rework. The Field Inspector should verify that the reworked units came from the original manufacturer (the Factory ID (if any) should be verified). The Field Inspector should verify that the new product label includes all required markings as shown in the Markings and Instructions section.	